



# Chicago Pneumatic

## SUPERLATIVE PERFORMANCE & ERGONOMICS



**AUTOBALANCER**



**★  
UNIQUE  
FEATURES**  
*Premium Tool*

**9560:-**

**CP3650-120AA5VK**

Art nr 6151607180

- ✓ Spindle thread:.....M14
- ✓ Wheel size: ..... 125 mm
- ✓ Power: ..... 1700 W
- ✓ Free speed: ..... 12000 rpm
- ✓ Length: ..... 238 mm
- ✓ Weight: ..... 1,9 kg

**INDUSTRIAL  
TOOLS**

FOR GENERAL & INDUSTRIAL MAINTENANCE,  
MANUFACTURING & HEAVY PRODUCTION

**SPECIAL OFFER  
SPRING 2017**

People. Passion. Performance.



*Dust-proof (IP6)  
and ATEX certified*

**CP6748EX-P11R ATEX**

Art nr 6151590570

**CP6768EX-P18D ATEX**

Art nr 6151590580

**CP6778EX-P18D ATEX**

Art nr 6151590590



**BENEFITS · CP6748EX 1/2"**

- ✓ Working Torque Range (fwd): 180-760 Nm
- ✓ Maximum Torque (reverse): 1085 Nm
- ✓ Free speed: 8400 rpm
- ✓ Blows per minute: 1200
- ✓ Weight : 2,4 kg

**3160:-**

**BENEFITS · CP6768EX 3/4" & CP6778EX 1"**

- ✓ Working Torque Range (fwd): 400-1400 Nm
- ✓ Maximum Torque (reverse): 1750 Nm
- ✓ Free speed: 5100 rpm
- ✓ Blows per minute: 1050
- ✓ Weight : 4,4 & 4,6 kg

**6130:-**

**BENEFITS**

- ✓ Working Torque Range (fwd): 350-1290 Nm
- ✓ Maximum Torque (reverse): 1630 Nm
- ✓ Free speed: 6300 rpm
- ✓ Blows per minute: 900
- ✓ Length: 222 mm
- ✓ Weight : 5.5 and 5,6 kg

**CP6763 3/4"**

Art nr 6151590400

**3720:-**

**CP6773 1"**

Art nr 6151590410

**3720:-**



*Compact, Robust & Powerful*



*The Best  
Super Industrial 1"*

**BENEFITS**

- ✓ Working Torque Range (fwd): 1220-2440 Nm
- ✓ Maximum Torque (reverse): 3790 Nm
- ✓ Free speed: 3500 rpm
- ✓ Blows per minute: 650
- ✓ Length: 272 mm
- ✓ Weight: 10.5 kg

**22280:-**

**CP0611P RS 1"**

Art nr 6151590050



**BENEFITS**

- ✓ Working Torque Range (fwd): 1220-2440 Nm
- ✓ Maximum Torque (reverse): 3790 Nm
- ✓ Free speed: 3500 rpm
- ✓ Blows per minute: 1020
- ✓ Length: 360 mm
- ✓ Weight: 10.4 kg

**26410:-**

**CP0611-D28H 1"**

Art nr 6151590160



**41260:-**

**CP6120-D35H 1 1/2"**

Art nr 6151590120

*The most productive 1 1/2"*

**BENEFITS**

- ✓ Working Torque Range (fwd): 815-2,710 Nm
- ✓ Maximum Torque (reverse): 4880 Nm
- ✓ Free speed: 3500 rpm
- ✓ Blows per minute: 960
- ✓ Length: 420 mm
- ✓ Weight: 15.6 kg



# MATERIAL REMOVAL



**Angel Grinder  
CP3019-12AC**



**Sander  
CP3019-20AF**



**Sander  
CP3019-12AF**

MODEL	PART NUMBER	FREE SPEED	POWER	PAD Ø	COLLET SIZE	SPINDLE THREAD	FREE SPEED AIR CONS.	ACTUAL AIR CONS.	NET WEIGHT	AIR INLET	PRICE
		rpm	W	mm	mm	in.	l/s	l/s	kg	NPT	
CP3019-12AC	615 160 4070	12.000	375	---	6.35	---	3.2	8.0	0.51	1/4"	<b>5930:-</b>
CP3019-20AF	615 160 7090	20.000	375	75	---	1/4" UNC	8.3	3.0	0.63	1/4"	<b>5880:-</b>
CP3019-12AF	615 160 7080	12.000	375	75	---	1/4" UNC	9.3	5.7	0.63	1/4"	<b>5880:-</b>

PART NUMBER	CAPACITY	PRICE
205 054 9913	2" (50mm)	<b>100:-</b>

*High performance in a compact package*

*High performance Industrial die grinder in a compact package*



**CP3019-20 CNOMO**  
Art nr 6151600340

**4630:-**

- BENEFITS**
- ✓ Collet size: 6 mm
  - ✓ Free speed: 20000 rpm
  - ✓ Power: 249 W
  - ✓ Length & Weight: 169 - 363 mm · 0.4 - 0.6 kg



**CP3019-20ES CNOMO**  
Art nr 6151602210

**5620:-**

*High performance Industrial die grinder in a compact package*



**CP3119-22 CNOMO**  
Art nr 6151600410

**6030:-**

- BENEFITS**
- ✓ Collet size: 6 mm
  - ✓ Free speed: 22000 rpm
  - ✓ Power: 900 W
  - ✓ Length & Weight: 222 - 363 mm · 1.0 - 1.4 kg



**CP3119-22ES CNOMO**  
Art nr 6151602280

**8590:-**

# KINGS OF REMOVAL

**SUPERIOR TORQUE FOR MAXIMUM PRODUCTIVITY**



**12130:-**

## CP3850-85AH7VE

Art nr 6151704930

- ✓ Wheel size:..... 180 mm
- ✓ Spindle thread: .... HEX
- ✓ Free speed: ..... 8500 rpm
- ✓ Power: ..... 21000 W
- ✓ Weight: ..... 2,70 kg

## CP3850-65AH9VE

Art nr 6151704950

- ✓ Wheel size:..... 230 mm
- ✓ Spindle thread: .... HEX
- ✓ Free speed: ..... 6500 rpm
- ✓ Power: ..... 2100 W
- ✓ Weight: ..... 2,90 kg



**12710:-**

## CP3349-SALAVELE

Art nr 6151609130

- ✓ Spindle thread: .... 5/8-11
- ✓ Wheel size: ..... 230 mm
- ✓ Free speed: ..... 6500 rpm
- ✓ Power: ..... 3000 W
- ✓ Weight: ..... 4.4 kg



*Superlative performance  
in heavy applications*

**14160:-**

**GOOD**



**2650:-**

## CP7550-A

Art nr 8941075503

- ✓ Wheel size:..... 125 mm
- ✓ Spindle thread: ... M14
- ✓ Free speed: ..... 12000 rpm
- ✓ Power: ..... 840 W
- ✓ Weight: ..... 1,6 kg

**BETTER**



**4050:-**

## CP3450-12AA5

Art nr 6151604040

- ✓ Wheel size:..... 125 mm
- ✓ Spindle thread: ... M14
- ✓ Free speed: ..... 12000 rpm
- ✓ Power: ..... 810 W
- ✓ Weight: ..... 1,7 kg

**BEST**



**AUTOBALANCER**

**9560:-**

## CP3650-120AA5VK

Art nr 6151607180

- ✓ Wheel size:..... 125 mm
- ✓ Spindle thread: ... M14
- ✓ Free speed: ..... 12000 rpm
- ✓ Power: ..... 1700 W
- ✓ Weight: ..... 1,9 kg



# BRAND NEW LINE OF INDUSTRIAL PISTOL DRILLS

## INDUSTRIAL REVERSIBLE PISTOL DRILLS

**2120:-**

**CP1114R40**

Art nr 6151580340

- ✓ Chuck capacity: 10 mm
- ✓ Free speed: 4000 rpm
- ✓ Power: 400 W
- ✓ Max torque: 1.7 Nm
- ✓ Net weight: 1.3 kg

**2120:-**

**CP1114R26**

Art nr 6151580330

- ✓ Chuck capacity: 10 mm
- ✓ Free speed: 2600 rpm
- ✓ Power: 400 W
- ✓ Max torque: 5.5 Nm
- ✓ Net weight: 1.3 kg



Forward – reverse switch for easier drilling and reaming.



## REVERSIBLE INDUSTRIAL DRILLS NEVER FELT SO COMFORTABLE

**2890:-**

**CP1114R09**

Art nr 6151580320

- ✓ Chuck capacity: 13 mm
- ✓ Free speed: 900 rpm
- ✓ Power: 400 W
- ✓ Max torque: 16.8 Nm
- ✓ Net weight: 1.8 kg

**2890:-**

**CP1114R05**

Art nr 6151580310

- ✓ Chuck capacity: 13 mm
- ✓ Free speed: 500 rpm
- ✓ Power: 400 W
- ✓ Max torque: 25.2 Nm
- ✓ Net weight: 1.8 kg

**BURR KIT**

MODEL	PART NUMBER	SCHANK	PCS	PRICE
POWER CUT	8940171786	6 mm	5	<b>1820:-</b>
DOUBLE CUT	8940171787	6 mm	5	<b>1490:-</b>
ALUMINIUM CUT	8940171788	6 mm	5	<b>1490:-</b>



**POWER  
CUT**



**DOUBLE  
CUT**



**ALUMINIUM  
CUT**



**1050:-**

**Needle Scaler  
CP7115**

Art nr 8941071150

*Compact to reach small areas*

**BENEFITS**

- ✓ Good power/weight ratio
- ✓ Blows per minute: 2400
- ✓ Bore - Stroke: 23.5 mm - 11 mm
- ✓ Power: 1.8 joule
- ✓ Needle capacity: 19 x 1/8 (3)
- ✓ Length - Weight: 340 mm - 2.7 kg



**2150:-**

**Belt Sander  
CP9780**

Art nr 6151939780

*Easy handling & large removal*

**BENEFITS**

- ✓ Quick-change belt replacement
- ✓ Paper size: 20x520
- ✓ Free speed: 20000 rpm
- ✓ Power: 380 W
- ✓ Length: 380 mm
- ✓ Weight : 1.5 kg





**TITAN**  
BY CHICAGO PNEUMATIC

**Titan hydraulic  
torque wrenches:  
T Series**

More info at: [www.titanti.com](http://www.titanti.com)



## HOSE REELS



**A**

- Extreme Robustness
- Made for All Purposes
- Adapted even to Industrial Uses



**B**

- Open
- More adapted to dirty environments
- Still Great Robustness and For All Purposes

PIC. REF	DESCRIPTION	PART NUMBER	THREAD	HOSE LENGTH (m)	Ø INT. (mm)	MATERIAL	PRICE
A	BSP HR8108	8940171991	1/4"	10	8	Composite	1880:-
A	BSP HR8208	8940171995	1/4"	10	8	Aluminum	2250:-
A	BSP HR8110	8940171993	1/4"	16	10	Composite	1640:-
A	BSP HR8210	8940171997	1/4"	16	10	Aluminum	3380:-
B	BSP HR9110	8940172001	3/8"	21	10	Composite	4880:-
A	BSP HR8113	8940171999	1/2"	16	13	Composite	3740:-
B	BSP HR9113	8940172003	1/2"	16	13	Composite	5240:-

## AIR FLEX

Aimed to improve the working ergonomoy, Air flex connectors can rotate 360° eliminating efforts when working in cramped spaces



MODEL	PART NUMBER	RECOMMENDED FLOW - MAX	PRICE
		l/s	
1/4"	894 017 1568	12	610:-
3/8"	894 017 1570	35	780:-
1/2"	894 017 1566	35	780:-

## SWIVEL



Aimed to improve the working ergonomoy, Air flex connectors can rotate 360° eliminating efforts when working in cramped spaces.

MODEL	PART NUMBER	PRICE
SWIVEL	894 015 8412	180:-



## OIL AND GLOVES

DESCRIPTION	PART NUMBER	PRICE
Air Tool Oil - 120 ml	CA149661	40:-
CP Gloves L	8940158618	370:-
CP Gloves XL	8940158619	370:-

## BLOW GUN

DESCRIPTION	PART NUMBER	PRICE
Blow gun standard	615 811 2690	160:-
Blow gun standard silencer	615 811 2700	170:-
Blow gun extended nozzle	615 811 2710	160:-
Blow gun extended nozzle silencer	615 811 2720	210:-



## COUPLINGS AND FILTERS, REGULATORS, LUBRICATORS (FRL) – CHECK OUR MAIN CATALOG



Regulator adjusting knob

1/4", 3/8" and 1/2" NPT and BSP sizes

Protect gauge Always on the right position

Aluminium body



Oil adjustment

Oil fill plug

Bowl guard with integral plastic bowl

Semi automatic drain

# BRAND NEW LINE RELEASED SPRING 2017: CPN series (Comfortable Pneumatic Nutrunner)

More info to come...

MODEL	SQUARE DRIVE	MAX TORQUE	WEIGHT
CP6613	3/4"	1300	4,4 kg
CP6626	1"	2600	5,7 kg
CP6641	1"	4100	9,9 kg
CP6681	1½"	8100	15,0 kg



- THE MOST ROBUST PNEUMATIC NUTRUNNER
- NO IMPACT – CONTINUOUS ROTATION FOR HEAVY DUTY FASTENING
- AMONG THE SMALLEST GEARBOX
- THE HIGHEST ACCURACY WITH THE AIR TORQUE CONTROL FRL PACK (ATC PACK)

Easily find the tools you need  
to get the job done!



## CP ToolBox



Get the free **CP ToolBox**  
Scan this QR code or visit [www.cp.com/app](http://www.cp.com/app)



Order the complete catalogue at  
[order.seo@cp.com](mailto:order.seo@cp.com) or from your dealer.

**ORDER DIRECT: POST@NTT.NO**  
**KONTAKT: DISTRIKTSANSVARIG**



Trykkluft- og verktøyteknikk

NTT AS, Skien – Tlf: 35905770 – [post@ntt.no](mailto:post@ntt.no) – [www.ntt.no](http://www.ntt.no)

Distributor